Parquet Les Élégants V4
technical characteristics

BERRY ALLOC

product specifications

		XXL 2,5
Format (l x w)	mm	1 180 x 187
Total thickness	mm	13
Bevel	-	4
Installation system	-	BestLoc X-Treme, no glue, no tools
Usage class	NF B53-669	33*
Residential use guarantee	-	15 years
Pack content	-	8 planks 1,765 m² 19,16 kg
Pallet content	-	36 packs 63,54 m² 711 kg

* heavy commercial use

composition

Surface treatment	-	Ultimtec® high performance varnish
Oak facing thickness	mm	2,5 oak
Intermediate layer	-	HDF
Backing	-	Softwood veneer

test results

Resistance to abrasion	NF B53-669	≥ 4
Impact resistance	NF B53-669	≥ 250 mm
Thickness swelling (HDF)	EN 317	< 12%
Moisture level	-	8 % (tol +/- 2)
Fire resistance	EN 13501-1 (oak)	Cfl-s1
Formaldehyde emissions	EN 717-1	E1
Slip resistance	EN 16165 (an. A & B)	PN 12, PC 6
Density	-	875 kg/m³
Resistance to chemical agents	NF B53-669	≥ 50
Effect of a castor chair	NF B53-669	> 25 000 Cycles
Thermal resistance in combination with underlay Excellence Plus	-	0.074 m²K/W
		Suitable for underfloor heating, see specific installation instructions : www.berryalloc.com

EPD INTERNATIONAL EPD SYSTEM

FDES VÉRIFIÉE inies

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+

PEFC

made in France

www.berryalloc.com

parquet.