ABET LAMINATI

# TABELLA RIASSUNTIVA CLASSIFICAZIONE FUOCO SECONDO EN 13501 -1 (PER MARCATURA CE) REV. 7
## *CHART OF FIRE CLASSIFICATION ACCORDING TO EN 13501-1 (FOR EC MARKING) REV. 7*

<table>
<tr><th>PRODOTTO<br>PRODUCT<br>SPESSORE<br>THICKNESS</th><th>MEG F1</th><th>STRATIF. F1</th><th>MEG STD</th><th colspan="2">STRATIF. STD</th></tr>
<tr><td>≥ 12 mm</td><td rowspan="2">B,s1-d0</td><td rowspan="2">B,s1-d0</td><td>B,s1-d0</td><td colspan="2">B,s1-d0</td></tr>
<tr><td>≥ 6 mm</td><td>C,s2-d0<br>telaio alluminio<br>aluminium frame</td><td>C,s2-d0<br>telaio<br>alluminio<br>aluminium frame</td><td>D,s2-d0<br>dichiarabile<br>senza prove<br>with no further testing</td></tr>
<tr><td>da 2 a < 6 mm</td><td>C,s2-d0<br>telaio all.<br>aluminium frame</td><td>B,s2-d0<br>telaio all.<br>aluminium frame<br>(prove in corso)</td><td>NON CERTIFICATO CE<br>NOT CE CERTIFIED<br>Probabile classe D<br>D class foreseen<br>(prove in corso su 4 mm)</td><td colspan="2">NON CERTIFICATO CE<br>NOT CE CERTIFIED<br>Probabile.classe D<br>D class foreseen<br>(prove in corso su 4 mm)</td></tr>
</table>

NOTA: Rimangono esclusi dalla certificazione ABET i laminati inferiori a 2 mm, sia nella versione standard che F1, e i prodotti speciali oggetto delle parti 8 e 9 della EN 438 (es. Diafos, Abetwood, Metalli, etc).
Il laminato sottile può essere marcato solo come composito. Poiché ABET ne produce solo lo strato decorativo, non può marcarlo ed è a carico del produttore del manufatto finito. Può accadere che i clienti chiedano ad ABET tale classe di reazione al fuoco a fini orientativi. Per questo sono state effettuate prove (Print HPL STD 0,7 mm su MDF da 6 mm ignifugo) e possiamo inviare una dichiarazione.

*NOTE: Laminates thinner than 2 mm, both standard and F1, are excluded by ABET certification, as well as the typologies of product dealt with in parts 8 and 9 of EN 438 (es Diafos, Abetwood, Metalli, etc).*
*Thin laminates can be marked as composite only. Since ABET produces only the decorative layer of it, it cannot mark and is up to the manufacturer of the finished product to do so. Some customers may ask for the fire classification to ABET at orienteering scope. Actually tests have been performed (Print HPL STD 0,7 mm combined to MDF 6 mm flame retardant) and we can send a declaration.*

27/05/2011